

PLEASE THINK BEFORE YOU PRINT


Specifications

Projection Audio System

Model SBA-L

Physical Specifications

Size	24" H × 5 1/8" W × 4" D (61 cm × 13 cm × 10.2 cm)
Weight (Both Speakers)	14 lb. 8 oz. (6.6 kg)
Shipping Weight	21 lb. (9.5 kg)
Shipping Size	8" H × 12 3/4" W × 26 1/2" D (20.3 cm × 32.4 cm × 67.3 cm)



All dimensions +/- 1/8" (0.3 cm). All weights +/- 2 lb. (0.9 kg).

Standard Features

Mounting Brackets	Mount the speakers directly to your SMART Board™ 685ix interactive whiteboard system.
Color	Dark gray (approximates Pantone® Charcoal Gray 18-0601 TPX) and silver
Connectivity	Dual RCA receptacles on the bottom of the right (active) speaker connect to the UX60 projector.
Frequency Range	50 Hz to 20 kHz ± 6 dB
Output	14 W RMS both channels driven simultaneously. The audio system provides a comfortable listening volume in rooms up to 1,000 ft ² (90 m ²) in size, with a 30-person capacity (subject to room acoustics).
Connection Panel (Right Speaker)	Polarized Molex® connector and 16 AWG wire with sufficient slack to discreetly route wire behind your interactive whiteboard or along the floor
Dual RCA Jacks	Connects to the UX60 projector
Power Connector	Powered barrel connector (15V DC, 4A), positive center
Power Requirements	Includes a switching power supply (100V–240V AC, 50/60 Hz, 1.5A) and a 14' 9 1/8" (4.5 m) country-specific power cord (15 V DC, 4000 mA, 60 VA, positive tip)

Extraordinary made simple™

SMART™

Environmental Compliance	China EIP, EU RoHS, EU WEEE, Packaging and US CPSIA
Regulatory Certifications	CE and CSA/UL
Warranty	One-year limited equipment warranty

Operating Specifications

41°F to 95°F (5°C to 35°C) with up to 80% humidity, non-condensing



CAUTION

If the speakers are very cold, allow them to warm to room temperature before operation.

SMART Order Numbers

SBA-L Projection Audio System for the SMART Board 685ix interactive whiteboard system

Physical Dimensions

