


Active USB Extension Cable

Specifications – USB-XT

Physical Specifications

Length	16' (5 m)
Module Size	2 3/8" W × 5 3/8" L × 1" D (60 mm × 135 mm × 27.6 mm)
Weight	5.3 oz (150 g)
Shipping Weight	1 lb. (450 g)
Shipping Size	2" H × 10 1/2" W × 9 3/8" D (508 mm × 267 mm × 238 mm)



All dimensions +/- 1/8" (0.3 cm).

Standard Features

USB Device Support	USB 2.0 high speed (up to 480 Mbps) and USB 1.1 (12 Mbps) devices. Recognized as one USB hub by the computer's operating system.
Compatibility	Windows® 2000 and XP, Windows Vista™, Mac OS 8.6 and later, and Linux® operating systems
Connectors:	One USB-A receptacle One USB-A plug
Power Supply	Bus powered from upstream hub or computer interface
Power Consumption	5 mA maximum, 3 mA typical
Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-40°F to 185°F (-40°C to 85°C)
Certifications and Regulatory Compliance	FCC, CE Class B, RoHS (Europe), WEEE
Warranty	One-year limited equipment warranty

SMART Order Number

USB-XT	Bus powered active USB extension cable
---------------	--

Installation Notes

You can use a maximum of four USB-XT extension cables to extend a 16' (5 m) USB cable to 80' (25 m).

NOTE: If you connect more than three USB-XT extension cables, you can exceed the USB specification limit of five hubs if your computer or a connected device has an internal hub. For example, the SMART Board™ 600i series interactive whiteboard system or SMART's SBA USB speaker system.

For more information about extending USB connections with the USB-XT extension cable, see document [99641](#).

SMART Technologies

1207 – 11 Avenue SW, Suite 300
Calgary, AB T3C 0M5
CANADA

www.smarttech.com/support www.smarttech.com/contactsupport
Support +1.403.228.5940 or Toll Free 1.866.518.6791 (Canada/U.S.)

