

Specifications

SMART Board 2075 Pro display

Model SBD-2075P


Overview

The SMART Board 2075 Pro display is a 75" non-touch LED display with built-in screen sharing that supports iOS, Android and Microsoft platforms.

The 4K ultra-high-definition display serves as an active collaboration hub between student and teacher devices to allow for greater levels of student engagement. The SMART Board Pro 2075 display is a cost-effective solution that offers businesses flexibility in their implementation of technology for group collaboration.

Dimensions and weights^{*}

Dimensions



Weight

69 lb 11 oz (31.6 kg)

Shipping weight
(including pallet)

109 lb. 9 oz. (49.7 kg)

Shipping
dimensions
(including pallet)

$73 \frac{3}{8}$ " W \times $49 \frac{1}{4}$ " H \times 11"

$\frac{1}{2}$ " D

$3 \frac{5}{8}$ " (9.3 cm) \times 186.4 cm \times 125.1 cm \times 29.3 cm

^{*}All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

Hardware

Screen sharing

Ethernet 10/100 Mbps LAN

Wireless 802.11 a/b/g/n

Dual-band 2.4/5 Ghz

Display

Aspect ratio 16:9

Optimal resolution 3840 × 2160 at 60 Hz

Contrast ratio (typical) 5000:1

Brightness (typical) 450 cd/m²

Refresh rate 60 Hz

Display type Full array LED

Response time 6.5 ms

Viewing angle 178°

UHD upscaling Yes

Supported video codecs H.264, H.265, VP8, VP9

Audio

Speakers 10 W integrated speakers (×2)

Noise level <30 dBA

Included cables and accessories Country-specific power cable
Remote control

Mounting holes For a standard VESA 600 mm × 400 mm mounting plate

Connectors

Back	HDMI in (×2)
	VGA in
	Component in
	DisplayPort in
	RCA audio in
	RCA audio out
	Stereo 3.5 mm audio line in
	Room control RS-232 in
	USB 2.0 A service port
	USB 2.0 A human interface device (HID) for connecting a keyboard or mouse during initial setup
	Ethernet RJ45

Installation requirements

Display	See the <i>SMART Board 2000 series display user's guide</i>
Room computer and guest laptops	
General requirements	See the SMART Meeting Pro release notes
4K UHD	Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory. See kb.smarttech.com/?q=15546
Mini-computers	
General requirements	See the SMART Meeting Pro release notes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Cable requirements

HDMI	HDMI 1.4 compliant or better
	Maximum length: 23' (7 m)
DisplayPort	DisplayPort 1.2 compliant or better
	Maximum length: 23' (7 m)
Important	Using cables that exceed these maximum lengths may produce unexpected results and degraded picture quality. Refer to the SMART installation standards (smarttech.com/kb/171035) for a comprehensive guide on cables and extensions for SMART hardware products.

Certification and compliance

Regulatory certification	TUV Rheinland (U.S./Canada), FCC, IC, CE
--------------------------	--

Environmental compliance

European Union	REACH, RoHS, WEEE and Packaging
U.S.	Packaging and Conflict Minerals

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Power consumption	
Standby mode	<0.3 W max
Normal operating	205 W
Operating temperature	41–95°F (5–35°C)
Storage temperature	-4–140°F (-20–60°C)
Humidity	10–80% relative humidity, non-condensing

Purchasing information

Order number

SBD-2075P	SMART Board 2075 Pro display with 10 licenses of SMART Meeting Pro PE software
------------------	--

Optional accessories

WM- SBID- 501	Fixed wall mount for SMART displays
---------------	-------------------------------------

Other	See smarttech.com/accessories
-------	--

Warranty	Three-year limited equipment warranty
-----------------	---------------------------------------

EWY1-SBD-2075P	One-year warranty extension
----------------	-----------------------------

EWY2-SBD-2075P	Two-year warranty extension
----------------	-----------------------------

smarttech.com/support
smarttech.com/contactsupport

© 2017 SMART Technologies ULC. All rights reserved. SMART Board, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. Contents are subject to change without notice. 09/2017

