

Specifications SMART Board® 6065-V2 interactive flat panel Model SPNL-6065-V2

Overview

The SMART Board® 6065-V2 interactive flat panel combines SMART's proprietary DVIT® (Digital Vision Touch) technology with a premium touch experience and the power of SMART Notebook® collaborative learning software on a 65" LED display. For simple and powerful digital whiteboarding, this interactive flat panel is also SMART kapp iQ[™] enabled.

The 4K ultra-high-definition display provides optimal image clarity and wide viewing angles. With the new Pen ID[™] feature, you can assign different appearances to the pens and write or draw over any application in digital ink.



Object Awareness allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See education.smarttech.com for more information about this product.

Dimensions and weights¹

Dimensions

Image: Section of the sectio

Weight

134 lb. (60.9 kg) **Shipping dimensions (including pallet)** 69 1/4" × 49 5/8" × 11 7/8" (175.8 cm × 126.1 cm × 30.3 cm) **Shipping weight** 181 lb. (82.1 kg)



As an ENERGY STAR[®] certified signage display, the SMART Board 6065-V2 interactive flat panel meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

Hardware

Interaction

Touch technology	DViT technology
Multitouch capabilities	8 touches on Windows® and Mac computers ²
Gesture support	Windows 7, Windows 8.1 and Windows 10 operating systems OS X 10.9, 10.10 and 10.11 operating system software
Object awareness	Behavior adjusts automatically to whatever tool or object is being used, whether it's a pen, finger, eraser or palm.
Pen ID	Two people can write independently and simultaneously, using different colored ink.
Display	
Туре	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)
Horizontal frequency	26.97–75.0 kHz
Vertical frequency	23.9–60.32 Hz
Contrast ratio (typical)	5000:1
Brightness (maximum)	338 cd/m ²
Pixel pitch	0.372 mm × 0.372 mm
Gamut	68% of NTSC
Viewing angle	178°
Response time (typical)	8 ms
Presence detection	Presence detection sensor on the bottom frame
Audio	10 W integrated side-firing speakers (×2)
Noise level	<35 dBA
Included cables and accessories	8' (2.4 m) country-specific power cable 16' 5" (5 m) USB cable ³ Pen (×2)
Mounting holes	For a standard VESA® 300 mm × 400 mm mounting plate 13 3/4" (34.9 cm) from the bottom of the interactive flat panel
Mounting bracket depth	Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive flat panel to clear the wall

 $^2 \mbox{Requires SMART}$ Product Drivers to be installed, and some applications might not support 8 touches

³HDMI cable not included (See Installation requirements for HDMI cable requirements.)

Connectors

Side	Side connector panel: USB 2.0 Type-B (×3) HDMI 1.4 in (×2) DisplayPort in Stereo 3.5 mm out RS-232 in	Accessory slot: OPS interface supporting HDMI, DisplayPort and USB
Bottom Back	USB 2.0 Type-A AC power inlet	

Installation requirements

Interactive flat panel	See the SMART Board 6000 series interactive flat panels administrator's guide
	(smarttech.com/kb/170641)

Room computers and guest laptops

General requirements	See smarttech.com/SMARTNotebookReleaseNotes
4K UHD	Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory See kb.smarttech.com/?q=15546
HDMI cable	HDMI 1.4 compliant or better Maximum recommended passive length of 25' (7.6 m)
DisplayPort cable	DisplayPort 1.2 compliant or better
Mini-computers	
General requirements	See smarttech.com/SMARTNotebookReleaseNotes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Power consumption at 77°F (25°C)	
Standby mode	<2.2 W
Normal operating (out-of-box)	110 W
Maximum operating (with accessories)	189 W
Operating temperature	41–95°F (5–35°C)

SPECIFICATIONS SMART BOARD 6065-V2 INTERACTIVE FLAT PANEL – MODEL SPNL-6065-V2

Storage temperature	-4–140°F (-20–60°C)	
Humidity	5–80% relative humidity, non-condensing	
Certification and compliance		
Regulatory certification	UL (U.S./Canada), FCC, IC, CE, CCC, EAC, RCM, KC, SPRING, PSE	
Environmental compliance		
European Union	REACH, RoHS, WEEE and Packaging	
U.S.	Packaging and Conflict Minerals	
Purchasing information Order number		
SPNL-6065-V2	SMART Board 6065-V2 interactive flat panel, including a SMART Notebook software license key	
Optional accessories		
WM-SBID-501	Fixed wall mount for SMART interactive flat panels	
UGK-KAPPIQ-AM30-EDU	SMART kapp iQ for education appliance for SMART Board 6000 series interactive flat panels	
Other	See smarttech.com/accessories	
Warranty	Two-year limited equipment warranty	
Extended warranty		
EWY1-SPNL6065	One-year warranty extension	

EWY3-SPNL6065 Three-year warranty extension

smarttech.com/support smarttech.com/contactsupport

© 2016 SMART Technologies ULC. All rights reserved. SMART Board, SMART Notebook, SMART kapp iQ, DViT, Pen ID, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. HDMI and all associated logos are trademarks of HDMI Licensing, LLC. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 07/2016.