

Specifications SMART Board® 6075 interactive flat panel Model SPNL-6075

Overview

The SMART Board[®] 6075 interactive flat panel combines SMART's proprietary DVIT[®] (Digital Vision Touch) technology with a premium touch experience and the power of SMART Notebook[®] collaborative learning software on a 75" LED display. For simple and powerful digital whiteboarding, this interactive flat panel is also SMART kapp iQ[™] enabled.




The 4K ultra-high-definition display provides optimal image clarity and wide viewing angles. With the new Pen ID[™] feature, you can assign different appearances to the pens and write or draw over any application in digital ink.

Object Awareness allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See education.smarttech.com for more information about this product.

Dimensions and weights¹



Weight

185 lb. (84 kg) **Shipping dimensions (including pallet)** 75 3/8" × 54 3/8" × 14" (191.6 cm × 138 cm × 35.5 cm) **Shipping weight** 238 lb. (108 kg)



As an ENERGY STAR[®] certified signage display, the SMART Board 6075 interactive flat panel meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

SPECIFICATIONS SMART BOARD 6075 INTERACTIVE FLAT PANEL – MODEL SPNL-6075

Hardware

Interaction

Touch technology	DViT technology
Multitouch capabilities	8 touches on Windows® and Mac computers ²
Gesture support	Windows 7, Windows 8.1 and Windows 10 operating systems OS X 10.9, 10.10 and 10.11 operating system software
Object awareness	Behavior adjusts automatically to whatever tool or object is being used, whether it's a pen, finger, eraser or palm.
Pen ID	Two people can write independently and simultaneously, using different colored ink.
Display	
Туре	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)
Horizontal frequency	122–140 kHz (typically 135 kHz)
Vertical frequency	47–63 Hz (typically 60 Hz)
Contrast ratio (typical)	5000:1
Brightness (maximum)	360 cd/m ²
Pixel pitch	0.429 mm × 0.429 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms
Presence detection	Presence detection sensor on the bottom frame
Audio	10 W integrated side-firing speakers (×2)
Noise level	<35 dBA
Included cables and accessories	8' (2.4 m) country-specific power cable 16' 5" (5 m) USB cable ³ Pen (×2)
Mounting holes	For a standard VESA® 600 mm × 400 mm mounting plate 13 3/4" (34.9 cm) from the bottom of the interactive flat panel
Mounting bracket depth	Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive flat panel to clear the wall

 $^2 \mbox{Requires SMART}$ Product Drivers to be installed, and some applications might not support 8 touches

³HDMI cable not included (See Installation requirements for HDMI cable requirements.)

Connectors

Side	Side connector panel: USB 2.0 Type-B (×3) HDMI 1.4 in (×2) DisplayPort in Stereo 3.5 mm out	Accessory slot: OPS interface supporting HDMI, DisplayPort and USB
Bottom Back	RS-232 in USB 2.0 Type-A AC power inlet	

Installation requirements

Interactive flat panel	See the SMART Board 6000 series interactive flat panels administrator's guide
	(smarttech.com/kb/170641)

Room computers and guest laptops

General requirements	See smarttech.com/SMARTNotebookReleaseNotes
4K UHD	Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory See kb.smarttech.com/?q=15546
HDMI cable	HDMI 1.4 compliant or better Maximum recommended passive length of 25' (7.6 m)
Mini-computers	
General requirements	See smarttech.com/SMARTNotebookReleaseNotes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Power consumption at 77°F (25°C)	
Standby mode	<2 W
Normal operating (out-of-box)	<131 W
Maximum operating (with accessories)	315 W
Operating temperature	41–95°F (5–35℃)
Storage temperature	-4–140°F (-20–60°C)
Humidity	5–80% relative humidity, non-condensing

SPECIFICATIONS SMART BOARD 6075 INTERACTIVE FLAT PANEL – MODEL SPNL-6075

Certification and compliance

Regulatory certification	UL (U.S./Canada), FCC, IC, EMC, LV, VCCI, PSE, KC Mark
Environmental compliance	
European Union	REACH, RoHS, WEEE and Packaging
U.S.	Packaging and Conflict Minerals
Purchasing information	

Order number

SPNL-6075	SMART Board 6075 interactive flat panel, including a SMART Notebook software license key
Optional accessories	
WM-SBID-501	Fixed wall mount for SMART interactive flat panels
UGK-KAPPIQ-AM30-EDU	SMART kapp iQ for education appliance for SMART Board 6000 series interactive flat panels
Other	See smarttech.com/accessories
Warranty	Two-year limited equipment warranty
Extended warranty	
EWY1-SPNL-6075	One-year warranty extension
EWY3-SPNL-6075	Three-year warranty extension

smarttech.com/support smarttech.com/contactsupport

© 2016 SMART Technologies ULC. All rights reserved. SMART Board, SMART Notebook, SMART kapp iQ, DViT, Pen ID, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. HDMI and all associated logos are trademarks of HDMI Licensing, LLC. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 07/2016.