



Specifications

SMART Board® 8075i-G5-SMP interactive flat panel with optional SMART kapp iQ™ functionality

Model SBID8075i-G5-SMP


Overview

The SMART Board® 8075i-G5-SMP interactive flat panel combines SMART's proprietary DVIT® (Digital Vision Touch) technology with a premium touch experience and the power of SMART Meeting Pro® software. For simple and powerful digital whiteboarding, this interactive flat panel is also available with SMART kapp iQ™ functionality.

The 4K ultra-high-definition display provides optimal image clarity and wide viewing angles. With the new Pen ID™ feature, you can assign different appearances to the pens and write or draw over any application in digital ink.


Object Awareness allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See smarttech.com for more information about this product.



Dimensions and weights¹

Dimensions



Weight

185 lb. (84 kg)

Shipping dimensions (including pallet)

75 3/8" × 54 3/8" × 14"
(191.6 cm × 138 cm × 35.5 cm)

Shipping weight

238 lb. (108 kg)



As an ENERGY STAR® certified signage display, the SMART Board 8075i-G5 interactive flat panel meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg).

Hardware

Interaction

Touch technology	DViT technology
Multitouch capabilities	8 touches on Windows® computers ²
Gesture support	Windows 7, Windows 8.1 and Windows 10 operating systems
Object awareness	Behavior adjusts automatically to whatever tool or object is being used, whether it's a pen, finger, eraser or palm.
Pen ID	Two people can write independently and simultaneously, using different colored ink.

Display

Type	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)
Horizontal frequency	122–140 kHz (typically 135 kHz)
Vertical frequency	47–63 Hz (typically 60 Hz)
Contrast ratio (typical)	5000:1
Brightness (maximum)	360 cd/m ²
Pixel pitch	0.429 mm × 0.429 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms



Presence detection Presence detection sensor on the bottom frame

Audio 10 W integrated side-firing speakers (×2)

Noise level <35 dBA

Included cables and accessories
 8' (2.4 m) country-specific power cable
 16' 5" (5 m) USB cable
 20' 8" (6.3 m) HDMI cable
 CAT 5 USB extender
 Pen (×2)

Mounting holes For a standard VESA® 600 mm × 400 mm mounting plate
 13 3/4" (34.9 cm) from the bottom of the interactive flat panel

Mounting bracket depth Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive flat panel to clear the wall

²Requires SMART Product Drivers to be installed, and some applications might not support 8 touches

Connectors

Side	Side connector panel: USB 2.0 Type-B (×3) HDMI 1.4 in (×2) DisplayPort in Stereo 3.5 mm out RS-232 in	Accessory slot: OPS interface supporting HDMI, DisplayPort and USB
Bottom	USB 2.0 Type-A	
Back	AC power inlet	

Installation requirements

Interactive flat panel	See the <i>SMART Board 8000i-G5-SMP series interactive flat panels administrator's guide</i> (smarttech.com/kb/170814)
-------------------------------	---

Room computers and guest laptops

General requirements	See smarttech.com/SMARTMeetingProReleaseNotes
4K UHD	Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory See kb.smarttech.com/?q=15546

Mini-computers

General requirements	See smarttech.com/SMARTMeetingProReleaseNotes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
---------------------------	---------------------------------

Power consumption at 77°F (25°C)

Standby mode	<2 W
Normal operating (out-of-box)	<131 W
Maximum operating (with accessories)	315 W

Operating temperature	41–95°F (5–35°C)
------------------------------	------------------

Storage temperature	-4–140°F (-20–60°C)
----------------------------	---------------------

Humidity	5–80% relative humidity, non-condensing
-----------------	---

Certification and compliance

Regulatory certification UL (U.S./Canada), FCC, IC, EMC, LV, VCCI, PSE, KC Mark

Environmental compliance

European Union REACH, RoHS, WEEE and Packaging

U.S. Packaging and Conflict Minerals

Purchasing information

Order number

SBID8075i-G5-SMP SMART Board 8075i-G5-SMP interactive flat panel, including a SMART Meeting Pro software room license and 25 SMART Meeting Pro software personal licenses

Optional accessories

WM-SBID-501 Fixed wall mount for SMART interactive flat panels

UGK-KAPPIQ-AM30-ENT SMART kapp iQ for business appliance for SMART Board 8000i-G5 series interactive flat panels

Other See smarttech.com/businessaccessories

Warranty

Three-year limited equipment warranty

SMART advanced support

Designed to limit downtime and optimize return on investment, SMART Support Services provide peace of mind and maximize the performance of your SMART solution. These offerings give you access to expert support, guaranteed response times and advance hardware replacement. Three service offerings are available: Basic, Elite and Platinum. For more information, see smarttech.com/services.

smarttech.com/support
smarttech.com/contactsupport

© 2016 SMART Technologies ULC. All rights reserved. SMART Board, SMART kapp iQ, SMART Meeting Pro, DVIT, Pen ID, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. HDMI and all associated logos are trademarks of HDMI Licensing, LLC. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 08/2016.